



13 Colorways:	T122-08 Frosted T122-12 Washed T122-14 Maple T122-16 White Oak T122-42 Ash T122-44 Teak T122-46 Beam	T122-48 Walnut T122-50 Rosewood T122-51 Cashmere T122-91 Weathered T122-95 Smoked T122-99 Charred	
Designer	Koroseal		
Total Weight	20.0 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	52 in.
Tensile (Minimum)	50 x 55 lb <sub>f</sub> (222 x 245 N)	Match Information	Non-Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb <sub>f</sub> (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	<p>NFPA 101® Life Safety Code®</p> <p>NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test<sup>1</sup> - Class A Rating</p> <p>NFPA 286 Corner Burn Test<sup>2</sup> - Meets requirements for Flame Spread, Smoke Developed, and Flashover</p> <p><small>1 When applied to GRC board with A-848-B adhesive    2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive</small></p>		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices		
For additional technical information please visit <a href="http://koroseal.com">koroseal.com</a>			

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | [koroseal.com](http://koroseal.com)

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.  
©2024 Koroseal Interior Products, LLC.