



8 Colorways:	ZF21-01 Glacier ZF21-02 Haze* ZF21-03 Ember* ZF21-04 Basalt*	ZF21-05 Hone* ZF21-06 Cobble* ZF21-07 Kaolin* ZF21-08 Terrain*
	Zi Zi O- Dasan	Zi Zi oo iciiaiii

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

NFPA 101® Life Safety Code®

NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test¹

- Class A Rating

- Flame Spread - 10

Fire Testing - Smoke Developed - 5

NFPA 286 Corner Burn Test²

- Meets requirements for Flame Spread, Smoke Developed, & Flashover

1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 - Meets emission requirements for schools and offices