

KOROSEAL.





	16 Colorways:	2N21-18 Clueless 2N21-28 Fascination 2N21-33 Liaisons	2N21-61 Rogue 2N21-65 Slingback	2N21-97 Allure
--	---------------	---	------------------------------------	----------------

^{*}These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Sondra Alexander™		
Total Weight	21.0 oz. ply (651 g. plm.) 14.0 oz. psy (474 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 50 lb _f (222 x 222 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408A, Type II	ASTM F-793	Category V, Type II

NFPA 101® Life Safety Code®

NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test¹

- Class A Rating

Fire Testing

NFPA 286 Corner Burn Test²

- Meets requirements for Flame Spread, Smoke Developed, and Flashover $\,$

1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com