

Clodagh for Koroseal®

3875 Embassy Parkway
Fairlawn, OH 44333

855.753.5474 koroseal.com

Trail

FACT SHEET

Reminiscent of a walk through a dense pine forest, Trail is an abstract representation of Clodagh's hikes with her son through the fragrant Oregon woods. A splash of color or a contrast in black and white, Trail is a graphic design that's sure to get attention. Trail uniquely adds a unique, natural element to the wall.

	US UNITS	METRIC UNITS
Total Weight	20.0 oz. PLY	620 g PLM 451 g PSM
Roll Width	52" – 54"	132 cm - 137 cm
Backing	Woven	
Tensile (minimum)	50 x 55 lb _f	222 x 245 N
Tear (minimum)	22 x 25 lb _f	111 x 111 N
Federal Spec.	CCC-W-408D, Type II	
WA Spec.	WA-101, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	ASTM E-84 Class A Rating Flame Spread – 0 Smoke Developed - 0 NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical 24" Horizontal 52" Nominal Information 52" Match Information Non-Reverse Hang, Random Match	
1 When applied to GRC board		2 When applied to 5/8" Type-X-Gypsum board

Available in 10 Colorways

CL05-10 Granite	CL05-05 Basalt
CL05-01 Frost	CL05-06 Core
CL05-02 Creek	CL05-07 Hansa
CL05-03 Spruce	CL05-08 Russet
CL05-04 Clay	CL05-09 Bark