



5 Colorways:	67530 67531 67532 67533* 67534*		
*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.			
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	33 in.
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	52 in.
Backing	Non-Woven	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Non-Reverse Hang, Straight Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating - Flame Spread - 10 - Smoke Developed - 5 NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, & Flashover 1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices		

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
 Arte® is a registered trademark of Arte N.V.
 NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association
 ©2023 Koroseal Interior Products, LLC.