

The word means flame. Dancing under a linen facade, Fuego comes to life in deep copper, aquamarine blue and soft gray and white hues. Fuego is a mixture of classic and contemporary, beautifully meshed together for an interesting pattern effect.

	US UNITS	METRIC UNITS
<b>Total Weight</b>	20 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
<b>Roll Width</b>	52" – 54"	132 - 137cm
<b>Gauge</b>	.022"	0.56 mm
<b>Fabric</b>	Woven	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	111 x 111 N
<b>Federal Spec</b>	CCC-W-408A, Type II	
<b>WA Spec</b>	WA 101 - 2011, Type II	
<b>ASTM F-793</b>	Category V, Type II	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® ASTM E-84 Tunnel Test <sup>1</sup> Class A Rating NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed & Flashover	
<b>CE Certification</b>	EU classification in accordance with EN15102:2007 + A1:2011 Fire Behavior – B Smoke Production – s <sup>2</sup> Flame Droplets – d <sup>0</sup>	
<b>Repeat</b>	Vertical N/A Horizontal N/A Nominal Pattern Width 51" Match Information Reverse Hang	
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

## Available in 11 Colorways

67310 \*67315  
\*67311 \*67316  
\*67312 \*67317  
\*67313 \*67318  
\*67314 \*67319  
\*67320

\* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.