



9 Colorways:	67160	67164*	67168*
	67161	67165	67170*
	67163*	67167*	67171
	6/163*	0/10/~	6/1/1

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Arte®			
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	39 in.	
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	26 in.	
Backing	Woven (Osnaburg)	Nominal Pattern Width	52 in.	
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Non-Reverse Hang, Straight Match	
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II	
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code®			
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating			
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, and Flashover			
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive			
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011			

For additional technical information please visit koroseal.com

Indoor Air Quality

California 01350 – Meets emission requirements for schools and offices