

ECO-A.R.T.TM by HYTEX[®]

ACOUSTIC RECYCLED TEXTILES

Wallcoverings • Panels • Partitions

A dimensional fabric produced with post-consumer recycled fiber offering exceptional performance, unmatched fade resistance, and a fire/smoke retardant Class A rating. It is lightweight and easy to install and maintain.

ECO-A.R.T.TM is moisture resistant, mildew, rot, and bacteria resistant and is nonallergenic.

-
- **eco-fi[®]** Polyester staple fiber. High strength fibers which are resistant to shrinking and stretching. Highly durable. 100% post-consumer recycled content from water & soda bottles.
 - Easy to clean and maintain.
 - Fiber does not absorb moisture
 - Acoustical qualities: NRC ratings .05 (ASTM C423)
 - Passes UBC 8-2/NFPA 265 Corner Burn Test. It is the standard test method for evaluating room fire growth contribution of Textile Wallcovering.
 - Solution dyed. Resists sun, fading - colors are fast to most destructive agents.

APPLICATIONS

DESIGNERS	HEALTH CARE	HOSPITALITY	CORPORATE	INSTITUTIONAL	ENTERTAINMENT
Commercial	Retirement	Ball Rooms	Executive	Schools(Auditorium)	Theatres
Interiors	Facilities	Conference	Conference	Government &	Recreational
Market	Nursing Homes	Rooms	Rooms	Mass Trans. Buildings	Centers
	Hospitals	Meeting Rooms	General Offices	Day Care Centers	
	Nursing Stations				

Acoustical Panels • Tack Boards • Elevators • Ceiling Tiles • Office Partitions • Chair Rails

COPPERSMITH SPECIFICATIONS

CONTENT	BACKING	WEIGHT	WIDTH	ROLL SIZE	FLAMMABILITY
eco-fi [®]	Radiant Fused	13 ounces /	54"	50 yards	Class A/ASTM E-84
Post-Consumer		face weight			UBC 8-2
Recycled Solution Dyed					Flame spread: 20 / Smoke: 30
Polyester Staple Fiber					
NRC	MOISTURE REGAIN	COLORFASTNESS TO LIGHT	ABRASION RESISTANCE		
(ASTM C-423)	(ASTM D-2654)	(AATCC-16A)	(ASTM D-4158)		
.05	.3%	Class 5 - 100 hours	Voluntary Prod. TS198		
over gypsum board			Full Commercial Serviceability		

