

Feathergrain is a multi-colored print with the look of wood. In atypical wood colors, it still provides a pleasing yet decorative look for the wall.

	US UNITS	METRIC UNITS
Total Weight	20.0 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
Roll Width	52/54 in.	132/140 cm
Gauge (avg)	0.021 in.	0.53 mm
Fabric	Osnaburg	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	
Federal Spec	CCC-W-408D, Type II	
WA Spec	WA-101, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover EU classification in accordance with EN 13501-1:2007 and EN15102-2008	
Indoor Air Quality	California 01350- Meets emission requirements for schools and offices	
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 51 in. 132 cm Random Match, Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

Available in 15 Colorways

F121-76 Ash	F121-28 Maple
F121-30 Bamboo	F121-41 Oak
F121-44 Birch	F121-16 Poplar
F121-72 Blue Spruce	F121-91 Rosewood
F121-61 Cherry	F121-53 Teak
F121-90 Cypress	F121-58 Walnut
F121-56 Driftwood	F121-75 Weathered Blue
F121-84 Evergreen	

Vinyl wallcovering has a multitude of characteristics that allow it to provide an attractive and serviceable wall surface. One of the characteristics of vinyl wallcoverings is very low moisture permeability. Therefore, it is important to assure that there are no deficiencies in the design, construction and maintenance of a building that allows moisture to accumulate in a wall cavity. The use of a vinyl wallcovering in such a deficient circumstance would result in the vinyl wallcovering acting as a vapor barrier and restricting the passage of the moisture and increasing the chance of mold growth. It is recommended that walls be checked with a suitable moisture meter prior to installation and the moisture content should not exceed 4%. Wallcovering should not be installed on a wall until water/moisture incursion has been eliminated. On renovation projects, examine walls that are to receive wallcovering and assure they do not exhibit any mold/mildew. All mold and mildew must be removed and surfaces treated to inhibit future growth. In order to reduce the risk of mold/mildew, Koroseal Interior Products, LLC utilized an inhibitor in the wallcovering. The company can also provide a service of microventing the wallcovering whereby more than 25,000 micro-holes /ft² are fused through the vinyl thereby making it permeable.