



8 Colorways:	ZF21-01 Glacier ZF21-02 Haze* ZF21-03 Ember*	ZF21-05 Hone* ZF21-06 Cobble* ZF21-07 Kaolin*
	ZF21-04 Basalt*	ZF21-08 Terrain*

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Koroseal			
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	N/A	
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A	
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.	
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Random Match	
Tear (Minimum)	25 × 25 lb _f (111 × 111 N)	WA Spec.	WA-101, Type II	
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test¹ - Class A Rating NFPA 286 Corner Burn Test² - Meets requirements for Flame Spread, Smoke Developed, and Flashover 1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive			
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011			
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices			

For additional technical information please visit koroseal.com