



*This decorative metallic wallcovering should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Arte®		
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 × 25 lb _f (111 × 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	NFPA 101® Life Safety Code®		
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating		
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, and Flashover		
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices		

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com