



8 Colorways:  
UPL1-01  
UPL1-06  
UPL1-12  
UPL1-13  
UPL1-14  
UPL1-15  
UPL1-16  
UPL1-19

Designer	Koroseal		
Total Weight	35.0 oz. ply (992 g. plm.) 22.4 oz. psy (635 g. psm.)	Vertical Repeat	N/A
Roll Width	52 in. (132 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	52 in.
Tensile (Minimum)	N/A	Match Information	Reverse Hang, Straight Match
Tear (Minimum)	N/A	WA Spec.	WA-101, Type III
Federal Spec.	CCC-W-408D, Type III	ASTM F-793	Category VI, Type III
Fire Testing	NFPA 101® Life Safety Code®		
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup> - Class A Rating		
	NFPA 286 Corner Burn Test <sup>2</sup> - Meets requirements for Flame Spread, Smoke Developed, & Flashover		
	<sup>1</sup> When applied to GRC board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices		
For additional technical information please visit <a href="http://koroseal.com">koroseal.com</a>			

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | [koroseal.com](http://koroseal.com)

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
Flex™ is a trademark of Koroseal Interior Products, LLC.  
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.  
©2024 Koroseal Interior Products, LLC.