



21 Colorways:	2R21-06 Miran 2R21-12 Astana Cream 2R21-15 Apsara 2R21-21 Canfu 2R21-25 Parthia Sands 2R21-27 Gobi Tan 2R21-33 Golden Shantung	2R21-36 Silk Road 2R21-40 Kashgar 2R21-51 Tashkent 2R21-58 Hunza Copper 2R21-63 Cinnabar 2R21-69 Turfan 2R21-73 Capsian Sea	2R21-80 Persian Sage 2R21-82 Loulan 2R21-85 Shache 2R21-86 Caravan 2R21-87 Zen Garden 2R21-94 Tianchi 2R21-98 Sichuan Grey
Designer	Koroseal		
Total Weight	15.0 oz. ply (466 g. plm.) 10.0 oz. psy (339 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.
Tensile (Minimum)	30 x 30 lb <sub>f</sub> (133 x 133 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	12 × 12 lb <sub>f</sub>	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408A, Type II	ASTM F-793	Category V, Type II
Fire Testing	NFPA 101 <sup>®</sup> Life Safety Code <sup>®</sup>		
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup> - Class A Rating		
	NFPA 286 Corner Burn Test <sup>2</sup> - Meets requirements for Flame Spread, Smoke Developed, and Flashover		
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices		
For additional technical information please visit koroseal.com			