

CHORDS

ACOUSTIC WALLCOVERINGS

Wallcoverings ♦ Panels ♦ Exhibits ♦ Partitions

Vertical channels texturize walls with professional-grade sound absorption made from post-consumer recycled fibers and styled in a modern designer palette.

SPECIFICATIONS

WIDTH:	54"	BACKING:	Fused Poly
TOTAL WEIGHT:	24 oz. per linear	INSTALLATION:	Non-Reversible / Random
THICKNESS:	yard	CONTENT:	Match Recycled Polyester
	Approximately	LENGTH:	33 yards
PERFORMANCE	4mm		

FLAMMABILITY:	Passes ASTM E-84 Class A Tested in Accordance with CAN/ULC-S102 Tested in Accordance with (EN13501): B-s1,d0 rating (after FR treatment by York) (AATCC Method 16): Class 5 (40 hours)
COLORFASTNESS TO LIGHT:	(AATCC Method 8): Class 4.5 (Wet), Class 4.5 (Dry)
COLORFASTNESS TO CROCKING:	Full Commercial Serviceability
ABRASION RESISTANCE:	0.20 over gypsum board
ACOUSTICAL NRC (ASTM C-423):	

QUALITY STANDARDS FIBER: ENVIRONMENTAL:	Does not absorb moisture. Solution dyed. Created with No PVC, No Heavy Metals or Formaldehyde,
SUSTAINABLE MATERIALS:	No ODS's, No Phthalates, No VOC's
CLEANING CODE:	Produced Using Recycled Content
INDOOR AIR QUALITY:	WS & BC – Water/Solvent & Bleach Cleanable Low V.O.C. Emitting Wallcoverings Meets California Department of Health Services Section 01350 Requirements for Office and School Interior
LEED CONTRIBUTION:	Can Contribute Towards LEED Points

Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation. For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

DESIGNERS

- Commercial Interiors Market

ENTERTAINMENT

- Theatres
- Recreational Centers

CORPORATE

- Executive Conference Rooms
- General Offices

INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center



WWW.KOROSEAL.COM

The assigned numerical reading and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire cognitions. Consult an architect or fire safety engineer for information on applicable building codes and reduction of fire hazards, including the use of sprinklers.