

	US UNITS	METRIC UNITS
<b>Total Weight</b>	15 oz PLY 10 oz PSY	464 g PLM 339 g PSM
<b>Roll Width</b>	52" – 54"	132 - 137cm
<b>Gauge</b>	.018"	0.457 mm
<b>Fabric</b>	Woven	
<b>Tensile (Minimum)</b>	30 x 30 lb <sub>f</sub>	133 x 133 N
<b>Tear (Minimum)</b>	12 x 12 lb <sub>f</sub>	
<b>Federal Spec</b>	CCC-W-408D, Type I	
<b>WA Spec</b>	WA-101, Type I	
<b>ASTM F-793</b>	Category IV, Type I	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® NFPA255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup> Class A Rating Flame Spread                      10 Smoke Developed                5 NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed and Flashover	
<b>CE Certification</b>	EU classification in accordance with EN 13501 – 1:2007 + EN15102:2008	
<b>Indoor Air Quality</b>	California 01350 – Meets emission requirements for schools and offices	
<b>Repeat</b>	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 51" Reverse Hang
1 When applied to GRC Board with A-848-B adhesive      2 When applied to 5/8" type-X gypsum board with A-848-B adhesive		

**Available in 20 Colorways**

67035   67021   67032  
 67028\*   67023   67027  
 67036   67022   67033  
 67039   67026   67029  
 67037\*   67030   67034  
 67038\*   67031\*   67020  
 67025   67024

\* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.