Koroseal®

3875 Embassy Parkway Fairlawn, OH 44333

855.753.5474 koroseal.com

Flexiweave FACT SHEET

Flexiweave is a new emboss for our Koroseal Basic line. Weaves give a visual and tactile effect that enhance our surroundings. Subtle weaves that suggest their presence but don't overwhelm the interior space is what Flexiweave was made to do. Intricately woven and colored in today's neutrals and accents, Flexiweave is appropriate for any surface.

		US UNITS	METRIC UNITS	
Total Weigh	t	20.0 oz. PLY	620 g PLM 451 g PSM	
Roll Width		52" – 54"	132 cm - 137 cm	
Backing		Woven		
Tensile (minimum)		50 x 55 lb _f	222 x 245 N	
Tear (minimum)		$22 \times 25 \text{ lb}_{\text{f}}$	111 x 111 N	
Federal Spec.		CCC-W-408D, Type II		
WA Spec.		WA-101, Type II		
ASTM F-793		Category V, Type II		
Fire Testing		ASTM E-84 Class A Rating Flame Spread – 10 Smoke Developed - 45		
		NFPA 286 Corner Burn Test ²		
		Meets requirements for Flame Spread, Smoke Developed and Flashover		
Indoor Air Quality		California 01350 – Meets emission requirements for schools and offices		
Repeat	Vertical Horizontal Nominal Information Match Information	N/A" N/A 52" Reverse Hang, Random N	√atch	
1 When applied to GRC board		2 When applied to 5/8" Type-X-Gypsum board		

Available in 18 Colorways

*FXW1-01 Strength	*FXW1-07 Dive	FXW1-13 Essential
FXW1-02 Breath	FXW1-08 Exhale	FXW1-14 Equilibrium
*FXW1-03 Balance	FXW1-09 Explore	*FXW1-15 Energize
FXW1-04 Submerge	FXW1-10 Appraise	*FXW1-16 Boost
*FXW1-05 Hike	FXW1-11 Retreat	*FXW1-17 Optimize
*FXW1-06 Trek	*FXW1-12 Stability	*FXW1-18 Core

^{*}These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.