

# Koroseal® DEALS

3875 Embassy Parkway  
Fairlawn, OH 44333

855.753.5474 koroseal.com

# DEALS SL24

## FACT SHEET

	<b>US UNITS</b>	<b>METRIC UNITS</b>
<b>Total Weight</b>	24.0 oz. PLY 16.0 oz. PSY	744 g PLM 542 g PSM
<b>Roll Width</b>	52/54 in.	132/137 cm.
<b>Gauge</b>	27 Mils	0.69 mm.
<b>Fabric</b>	Woven	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	
<b>Federal Spec</b>	CCC-W-408A, Type II	
<b>WA Spec</b>	WA-101, Type II	
<b>Fire Testing</b>	NFPA 101 <sup>®</sup> Life Safety Code <sup>®</sup> NFPA255 (UL723, CAN S102M) Tunnel Test <sup>1</sup> Class A Rating NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed and Flashover	
<b>Repeat</b>	Vertical Horizontal Match Information	N/A N/A Random Match, Reverse Hang

1 When applied to GRC Board with A-848-B adhesive      2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

## Available in 6 Colorways

SL24-03  
SL24-05  
SL24-20  
SL24-43  
SL24-95  
SL24-98