

Koroseal® DEALS

3875 Embassy Parkway
Fairlawn, OH 44333

855.753.5474 koroseal.com

DEALS S621

FACT SHEET

	US UNITS	METRIC UNITS
Total Weight	21.0 oz. PLY 14.0 oz. PSY	651 g PLM 475 g PSM
Roll Width	52/54 in.	132/137 cm.
Gauge	20.5 Mils	0.52 mm.
Fabric	Woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	
Federal Spec	CCC-W-408A, Type II	
WA Spec	WA-101, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical Horizontal Match Information	N/A N/A Random Match, Reverse Hang

1 When applied to GRC Board with A-848-B adhesive 2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

Available in 7 Colorways

- S621-60
- S621-09
- S621-29
- *S621-32
- S621-46
- *S621-85
- *S621-91

***These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.**