



|                    |   |                       |                            |
|--------------------|---|-----------------------|----------------------------|
| 12 Colorways:      | 67660   | 67666                 |                            |
|                    | 67661   | 67668                 |                            |
|                    | 67662   | 67669                 |                            |
|                    | 67663   | 67670                 |                            |
|                    | 67664   | 67671                 |                            |
|                    | 67665   |                       |                            |
| Designer           | Arte®   |                       |                            |
| Total Weight       | 20 oz. ply (618 g. plm.)<br>13.3 oz. psy (451 g psm.)   | Vertical Repeat       | N/A                        |
| Roll Width         | 52-54 in. (132-137 cm.)   | Horizontal Repeat     | N/A                        |
| Backing            | Woven (Osnaburg)  | Nominal Pattern Width | 51 in.                     |
| Tensile (Minimum)  | 50 x 55 lb <sub>f</sub> (222 x 245 N)   | Match Information     | Reverse Hang, Random Match |
| Tear (Minimum)     | 25 x 25 lb <sub>f</sub> (111 x 111 N)   | WA Spec.              | WA-101, Type II            |
| Federal Spec.      | CCC-W-408D, Type II   | ASTM F-793            | Category V, Type II        |
| Fire Testing       | NFPA 101® Life Safety Code®   |                       |                            |
|                    | NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup><br>- Class A Rating  |                       |                            |
|                    | NFPA 286 Corner Burn Test <sup>2</sup><br>- Meets requirements for Flame Spread, Smoke Developed, and Flashover       |                       |                            |
|                    | 1 When applied to GRC board with A-848-B adhesive    2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive |                       |                            |
| CE Certification   | EU classification in accordance with EN 15102:2007 + A1:2011  |                       |                            |
| Indoor Air Quality | California 01350 – Meets emission requirements for schools and offices  |                       |                            |

For additional technical information please visit [koroseal.com](http://koroseal.com)

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | [koroseal.com](http://koroseal.com)

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
Arte® is a registered trademark of Arte N.V.  
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.  
©2024 Koroseal Interior Products, LLC.