

Silk originated over 2000 years ago and remains one of the most beloved fabrics today. "Raw" silk refers to thread that has not been treated in any way; thread that when woven boasts a natural slub that “attracts” light. Patty magically incorporates this texture with a watered ombre to capture the beauty that is Fortuna Silk, an elegant design appropriate for multiple applications. Looking fresh from the loom, Fortuna Silk adds allure to any space it enrobes.

	US UNITS	METRIC UNITS
Total Weight	20.0 oz. PLY 13.3 oz. PSY	618 g PLM 451 g PSM
Roll Width	52” – 54”	132 cm - 137 cm
Gauge	.022”	0.559 mm
Fabric	Non-woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	111 x 111 N
Federal Spec.	CCC-W-408D, Type II	
WA Spec.	WA-101, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M)) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011 Rating – B s ¹ d ⁰	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical	24”
	Horizontal	N/A
	Nominal Information	51”
	Match Information	Non-Reverse, Straight Match
	1 When applied to GRC board with A-848-B adhesive	2 When applied to 5/8” Type-X-Gypsum board with A-848-B adhesive

Available in 2 Colorways

FS21-18 Harmonia
FS21-20 Atlas

Silk originated over 2000 years ago and remains one of the most beloved fabrics today. "Raw" silk refers to thread that has not been treated in any way; thread that when woven boasts a natural slub that "attracts" light. Patty magically incorporates this texture with a watered ombre to capture the beauty that is Fortuna Silk, an elegant design appropriate for multiple applications. Looking fresh from the loom, Fortuna Silk adds allure to any space it enrobes.

	US UNITS	METRIC UNITS
Total Weight	20.0 oz. PLY 13.3 oz. PSY	618 g PLM 451 g PSM
Roll Width	52" – 54"	132 cm - 137 cm
Gauge	.022"	0.559 mm
Fabric	Non-woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	111 x 111 N
Federal Spec.	CCC-W-408D, Type II	
WA Spec.	WA-101, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M)) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed & Flashover	
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011 Rating – B s ¹ d ⁰	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical 24" Horizontal N/A Nominal Information 51" Match Information Non-Reverse, Straight Match	
1 When applied to GRC board with A-848-B adhesive		2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

Available in 16 Colorways

- FS21-11 Alexandra
- FS21-14 Titans
- FS21-15 Helios
- FS21-08 Dorian
- FS21-10 Apollo
- FS21-17 Selene
- FS21-22 Evening Sky
- FS21-04 Cassandra
- FS21-16 Thalia
- FS21-07 Iris
- FS21-03 Athena
- FS21-06 Star
- FS21-12 Olympus
- FS21-09 Venetian
- FS21-19 Chloris
- FS21-02 Peacock Blue

These Mylar colors are not U.L. Rated and are not IMO Certified