



**21 Colorways:**

|                       |                    |                   |
|-----------------------|--------------------|-------------------|
| NM21-01 Silver Skies* | NM21-08 Fawn*      | NM21-15 Shadow*   |
| NM21-02 Coconut*      | NM21-09 Macaroon   | NM21-16 Anchor*   |
| NM21-03 Chiffon       | NM21-10 Nimbus*    | NM21-17 Sangria   |
| NM21-04 Juniper       | NM21-11 Desert*    | NM21-18 Cobalt*   |
| NM21-05 Haze          | NM21-12 Hazelwood* | NM21-19 Prussian* |
| NM21-06 Charmed       | NM21-13 Mocha*     | NM21-20 Abyss*    |
| NM21-07 Luster        | NM21-14 Celestial* | NM21-21 Iridium*  |

\*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

|                          |  |                              |                            |
|--------------------------|--|------------------------------|----------------------------|
| <b>Designer</b>          | Koroseal   |                              |                            |
| <b>Total Weight</b>      | 20.0 oz. ply (618 g. plm.)<br>13.3 oz. psy (451 g. psm.) | <b>Vertical Repeat</b>       | N/A                        |
| <b>Roll Width</b>        | 52-54 in. (132-137 cm.)                                  | <b>Horizontal Repeat</b>     | N/A                        |
| <b>Backing</b>           | Woven (Osnaburg)   | <b>Nominal Pattern Width</b> | 51 in.                     |
| <b>Tensile (Minimum)</b> | 50 x 55 lb <sub>f</sub> (222 x 245 N)                    | <b>Match Information</b>     | Reverse Hang, Random Match |
| <b>Tear (Minimum)</b>    | 25 x 25 lb <sub>f</sub> (111 x 111 N)                    | <b>WA Spec.</b>              | WA-101, Type II            |
| <b>Federal Spec.</b>     | CCC-W-408D, Type II                                      | <b>ASTM F-793</b>            | Category V, Type II        |

NFPA 101® Life Safety Code®

**Fire Testing**

NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test<sup>1</sup>  
- Class A Rating

NFPA 286 Corner Burn Test<sup>2</sup>  
- Meets requirements for Flame Spread, Smoke Developed, and Flashover

<sup>1</sup> When applied to GRC board with A-848-B adhesive    <sup>2</sup> When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

**CE Certification**    EU classification in accordance with EN 15102:2007 + A1:2011

**Indoor Air Quality**    California 01350 – Meets emission requirements for schools and offices

**For additional technical information please visit [koroseal.com](http://koroseal.com)**

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | [koroseal.com](http://koroseal.com)

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.  
©2024 Koroseal Interior Products, LLC.