



PW24-01 Selenite PW24-05 Seawater*
PW24-02 Alabaster PW24-06 Gypsum*
PW24-03 Flower* PW24-07 Satin Spar*
PW24-04 Desert Rose* PW24-08 Rock*

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Koroseal		
Total Weight	24 oz. ply (743 g. plm.) 16 oz. psy (542 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

NFPA 101® Life Safety Code®

NFPA 255 (ASTM E-84, CAN S102M) Tunnel $Test^1$

- Class A Rating

Fire Testing

NFPA 286 Corner Burn Test²

- Meets requirements for Flame Spread, Smoke Developed, & Flashover

 $1\ When applied to\ GRC\ board\ with\ A-848-B\ adhesive \\ 2\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 2\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ board\ with\ A-848-B\ adhesive \\ 3\ When\ board\ with\ A-848-B\ adhesive \\ 3\$

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit koroseal.com