

	<b>US UNITS</b>	<b>METRIC UNITS</b>
<b>Total Weight</b>	20 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
<b>Roll Width</b>	52" – 54"	132 - 137cm
<b>Gauge</b>	.025"	0.635 mm
<b>Fabric</b>	Non-Woven	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	111 x 111 N
<b>Federal Spec</b>	CCC-W-408A, Type II	
<b>WA Spec</b>	WA-101 - 2011, Type II	
<b>ASTM F-793</b>	Category V, Type II	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® NFPA 255 (UL723, CAN S102M) Tunnel Test <sup>1</sup> Class A Rating NFPA 286 Corner Burn Test <sup>2</sup>	
<b>CE Certification</b>	Meets requirements for Flame Spread, Smoke Developed & Flashover EU classification in accordance with EN15102:2007 + A1:2011	
<b>Indoor Air Quality</b>	California 01350 – Meets emission requirements for schools and offices	
<b>Repeat</b>	Vertical Horizontal Nominal Pattern Width Match Information	38.75" 25.56" 51" Straight Match, Non-Reverse Hang
2 When applied to 5/8" type-X gypsum board with A-848-B adhesive		
1 When applied to GRC Board with A-848-B adhesive		

**Available in 15 Colorways**

67470	67475	67480
67471	67476	67481
67472	*67477	*67482
67473	67478	67483
67474	67479	67484

**\*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.**