

	US UNITS	METRIC UNITS
Total Weight	15 oz PLY 10 oz PSY	464 g PLM 339 g PSM
Roll Width	52" – 54"	132 - 137cm
Gauge	.018"	0.457 mm
Fabric	Non-woven	
Tensile (Minimum)	30 x 30 lb _f	133 x 133 N
Tear (Minimum)	12 x 12 lb _f	
Federal Spec	CCC-W-408D, Type I	
WA Spec	WA-101, Type I	
ASTM F-793	Category IV, Type I	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (ASTM E-84, CAN S102M) Tunnel Test ¹ Class A Rating Flame Spread 10 Smoke Developed 5 NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
CE Certification	EU classification in accordance with EN 13501 – 1:2007 + EN15102:2008	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical N/A Horizontal N/A Nominal Pattern Width 51" Match Information Reverse Hang	
1	When applied to GRC Board with A-848-B adhesive	2
		When applied to 5/8" type-X gypsum board with A-848-B adhesive

Available in 17 Colorways

67047 67046 67055
67053 67040 67054
67048 67041 67051
67052 67049 67043
67044 67042 67056
67045 67050