STRATOS
Fact Sheet

12 Colorways:	47102 47104* 47105 47106 47107 47109	47110 47111 47115 47116 47117* 47118

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	**Vertical Repeat**	N/A
Roll Width	52-54 in. (132-137 cm.)	**Horizontal Repeat**	N/A
Backing	Woven (Osnaburg)	**Nominal Pattern Width**	51 in.
Tensile (Minimum)	50 x 55 lb_f (222 x 245 N)	**Match Information**	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb_f (111 x 111 N)	**WA Spec.**	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	**ASTM F-793**	Category V, Type II

Fire Testing

NFPA 101® Life Safety Code®

NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test[1]
- Class A Rating
- Flame Spread - 10
- Smoke Developed - 5

NFPA 286 Corner Burn Test[2]
- Meets requirements for Flame Spread, Smoke Developed, & Flashover

1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
Arte® is a registered trademark of Arte N.V.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association
©2023 Koroseal Interior Products, LLC.

57-47-3420-02/2014