

Classic, beautiful and durable enough to stand up to rough treatment. This illusion of natural woven cane or “Earth Fibers” illustrates Maya’s devotion to capturing depth and texture.

	US UNITS	METRIC UNITS
<b>Total Weight</b>	21.0 oz PLY 14.0 oz PSY	651 g PLM 474 g PSM
<b>Roll Width</b>	54 in.	137 cm
<b>Gauge</b>	28 Mils	0.71 mm
<b>Fabric</b>	Osnaburg	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	
<b>Federal Spec</b>	CCC-W-408A, Type II	
<b>WA Spec</b>	WA-101, Type II	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test <sup>1</sup> Class A Rating NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed and Flashover	
<b>Repeat</b>	Vertical Horizontal Match Information	N/A N/A Random Match, Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8” type-X gypsum board with A-848-B adhesive

## Available in 10 Colorways

PA21-15 Aruba	PA21-27 Moorea
PA21-36 Belize	PA21-18 Roseau
PA21-07 Dominica	PA21-50 St. John’s
PA21-10 Martinique	PA21-61 St. Lucia
PA21-23 Montego Bay	PA21-39 Trinidad