

Koroseal® DEALS

3875 Embassy Parkway
Fairlawn, OH 44333

855.753.5474 koroseal.com

DEALS 5542

FACT SHEET

	US UNITS	METRIC UNITS
Total Weight	12.0 oz. PLY 8.0 oz. PSY	372 g PLM 271 g PSM
Roll Width	52/54 in.	132/137 cm.
Gauge	19 Mils	0.48 mm.
Fabric	Sheeting	
Tensile (Minimum)	40 x 30 lb _f	178 x 133 N
Tear (Minimum)	14 x 12 lb _f	
Federal Spec	CCC-W-408A, Type I	
WA Spec	WA-101, Type I	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical Horizontal Match Information	N/A N/A Random Match, Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		
2 When applied to 5/8" type-X gypsum board with A-848-B adhesive		

Available in 8 Colorways

5542-39
5542-55
5542-60
5542-69
5542-73
5542-76
5542-86
5542-89