





HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES Wallcoverings • Panel Systems • Partitions

tilizing a combination of pre-consumer and post-consumer recycled polyester to create unique performance yarns, Hytex Industries introduces our newest collection of vertical surface textiles for the commercial market.

KOA SPECIFICATIONS

CONTENT
BACKING
FINISH
WEIGHT
WIDTH
ROLL SIZE

90% polyester
acrylic latex
CryptonWall® 'Green' 15 oz. 54"
50 yards
Soil & Stain
Repellant

15% RECYCLED CONTENT

- · 5% post-consumer (polyester)
- · 10% pre-consumer (olefin)

FLAMMABILITY

Class A / ASTM E-84 Passes: UBC 8-2 Passes: Cal 117 Passes: Vertical Burn

ABRASION RESISTANCE

(ASTM D-4157-02) 100,000 double rubs

COLOR FASTNESS TO LIGHT

(AATCC-16A) Class 5.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- · pvc
- · chlorene
- plasticizers
- · heavy metals
- · formaldehyde
- · ozone depleting substances
- · volatile organic chemicals (voc's)



recycled yarns by unifi

conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce

[®] Hytex Industries, Inc. 2015 All rights reserved.