



9 Colorways:	KLC-21799		KLC-22231	
	KLC-21856		KLC-22350*	
	KLC-21945		KLC-22457	
	KLC-22038		KLC-22554	
	KLC-22108			
*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.				
Designer	Koroseal			
Total Weight	21.0 oz. ply (651 g. plm.) 14.0 oz. psy (474 g. psm.)		Vertical Repeat	10 in.
Roll Width	53-55 in. (134-140 cm.)		Horizontal Repeat	10.3 in.
Backing	Woven (Osnaburg)		Nominal Pattern Width	51.5 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)		Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)		WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408A, Type II		ASTM F-793	Category V, Type II
Fire Testing	NFPA 101® Life Safety Code®			
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating			
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, and Flashover			
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive			
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011			
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices			
For additional technical information please visit koroseal.com				

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal[®] is a **registered trademark of Koroseal Interior Products, LLC.**
Morocco[®] is a **copyright of Koroseal Interior Products, LLC.**
NFPA 101[®] and Life Safety Code[®] are registered trademarks of National Fire Prevention Association.
©2024 Koroseal Interior Products, LLC.