



12 Colorways:	SG33-01	SG33-05	SG33-09
	SG33-02	SG33-06	SG33-10
	SG33-03	SG33-07	SG33-11
	SG33-04	SG33-08	SG33-12

Designer	Stacy Garcia New York		
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Non-Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

Fire Testing	NFPA 101® Life Safety Code®		
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating		
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, & Flashover		
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		

CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011
-------------------------	--

Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices LINK
---------------------------	--

Environmental Product Declaration	LINK
--	----------------------

Health Product Declaration (HPD)	LINK
---	----------------------

For additional technical information please visit koroseal.com

1111 Medina Road | Medina, OH 44256 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
© 2025 Koroseal Interior Products, LLC.