



8 Colorways:	CL08-01 Sleet CL08-02 Breeze CL08-03 Dew CL08-04 Fog	CL08-05 Blizzard CL08-06 Haze* CL08-07 Rainfall CL08-08 Thunder
	CLU8-04 F0g	CLU8-U8 I nunder

*This decorative metallic wallcovering should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Clodagh		
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	18 in.
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	52 in.
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Non-Reverse Hang, Straight Match
Tear (Minimum)	25 × 25 lb _f (111 × 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test¹ - Class A Rating NFPA 286 Corner Burn Test² - Meets requirements for Flame Spread, Smoke Developed, and Flashover 1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8° Type-X-Gypsum board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		

For additional technical information please visit koroseal.com

Indoor Air Quality

California 01350 – Meets emission requirements for schools and offices