



5 Colorways:  
PV26-05  
PV26-39  
PV26-43  
PV26-51  
PV26-56\*

\*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Koroseal		
Total Weight	26.0 oz. ply (806 g. plm.) 17.3 oz. psy (587.6 g. psm.)	Vertical Repeat	N/A
Roll Width	54 in. (137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	N/A
Tensile (Minimum)	50 x 55 lb <sub>f</sub> (222 x 245 N)	Match Information	Reverse Hang, Straight Match
Tear (Minimum)	25 x 25 lb <sub>f</sub> (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408A, Type II	ASTM F-793	Category V, Type II

NFPA 101® Life Safety Code®

Fire Testing

- NFPA 255 (ASTM E-84, CAN UL S102M) Tunnel Test<sup>1</sup>
  - Class A Rating
- NFPA 286 Corner Burn Test<sup>2</sup>
  - Meets requirements for Flame Spread, Smoke Developed, and Flashover

<sup>1</sup> When applied to GRC board with A-848-B adhesive    <sup>2</sup> When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification    EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality    California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit [koroseal.com](http://koroseal.com)

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | [koroseal.com](http://koroseal.com)

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.  
©2024 Koroseal Interior Products, LLC.