

# COMFORT ZONE WOOD DATA SHEET



Unite the highly effective acoustical performance of PET felt with the natural and attractive look of wood. Embrace continuity by creating a design that connects walls and ceilings. Installation is a breeze! Easily glue on, or screw directly into any existing ceiling or wall. Comfort Zone Wood comes in four woodgrain options with a True Black PET backing.

## SPECIFICATIONS

**Standard Panel Size:** 24" x 96"

**Thickness:** 0.87"

**Weight:** 35 lbs/Panel

## HARDWARE INCLUDED

Comfort Zone Wood comes ready to glue or screw to ceiling or wall

## FIRE RATING

Class B per ASTM E-84

## COMPOSITION

- 9mm 100% PET Felt
- MDF, Wood Veneer

## ENVIRONMENTAL FACTORS

- 100% Recyclable
- 55% Post-Consumer Recycled
- Low VOC Emissions
- CARB-Approved TPC
- FSC Chain and Custody Certified

## INSTALLATION OPTIONS

Comfort Zone Wood comes ready to glue or screw directly to any existing ceiling or wall. Screw directly on studs, and fit the screws between slats. Alternatively, Comfort Zone Wood can be cut to fit into a T-Grid similar to a typical dropped

WALL INSTALLATION  
WITH FURRING STRIPS

WALL INSTALLATION  
WITH ADHESIVE

CEILING INSTALLATION  
WITH FURRING STRIPS

DROP CEILING  
INSTALLATION

## ACOUSTICAL DATA

Comfort Zone Wood (22mm) no air gap: NRC = 0.55

Comfort Zone Wood (22mm) 1" air gap: NRC = 0.70

Comfort Zone Wood (22mm) 2" air gap: NRC = 0.80

Test reflects material ratings. Product testing according to standard mounting procedures coming soon.  
All NRC testing assumes one face/one object and does not account for the product thickness.