

A tiny, shrunken version of the running bond seen in masonry is combined with sheen and texture to create a simple but contemporary version akin to a woven fabric.

	US UNITS	METRIC UNITS
<b>Total Weight</b>	20.0 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
<b>Roll Width</b>	52/54 in.	132/137 cm
<b>Gauge (avg)</b>	0.24 in.	0.61 mm
<b>Fabric</b>	Non-Woven	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	111 x 111 N
<b>Federal Spec</b>	CCC-W-408D, Type II	
<b>WA Spec</b>	WA-101, Type II	
<b>ASTM F-793</b>	Category V, Type II	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup> Class A Rating Flame Spread      10 Smoke Developed   5 NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed and Flashover EU classification in accordance with EN 13501-1:2007 and EN-15102-2008	
<b>Indoor Air Quality</b>	California 01350 - Meets emission requirements for schools and offices	
<b>Repeat</b>	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 51 in. Random Match, Reverse Hang 130 cm
1 When applied to GRC Board with A-848-B adhesive      2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive		

### Available in 13 Colorways

GRAD-26 Ash	GRAD-35 Ecru
GRAD-22 Beige	GRAD-41 Falcon
GRAD-10 Bone	GRAD-59 Khaki
GRAD-50 Charcoal	GRAD-19 Linen
GRAD-57 Coconut	GRAD-75 Midnight
GRAD-72 Cornflower	GRAD-54 Quartz
GRAD-16 Cornsilk	