

	US UNITS	METRIC UNITS
Total Weight	20 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
Roll Width	52" – 54"	132 - 137cm
Gauge	.025"	0.635 mm
Fabric	Non-Woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	111 x 111 N
Federal Spec	CCC-W-408A, Type II	
WA Spec	WA-101 - 2011, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ²	
CE Certification	Meets requirements for Flame Spread, Smoke Developed & Flashover EU classification in accordance with EN15102:2007 + A1:2011	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	24" 26.5" 51" Random Match, Reverse Hang
	<p>1 When applied to GRC Board with A-848-B adhesive</p> <p>2 When applied to 5/8" type-X gypsum board with A-848-B adhesive</p>	

Available in 15 Colorways

67260	67265	67270
67261	67266	67271
67262	67267	67272
67263	67268	67273
67264	67269	67274