

	<b>US UNITS</b>	<b>METRIC UNITS</b>
<b>Total Weight</b>	20.0 oz. PLY 13.3 oz. PSY	618 g PLM 451 g PSM
<b>Roll Width</b>	52/54 in.	132/137 cm.
<b>Gauge</b>	.025 in.	0.635 mm.
<b>Fabric</b>	Woven	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	111 x 111 N
<b>Federal Spec.</b>	CCC-W-408D, Type II	
<b>WA Spec.</b>	WA-101, Type II	
<b>ASTM F-793</b>	Category V, Type II	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M)) Tunnel Test <sup>1</sup> Class A Rating Flame Spread - 10 Smoke Developed - 5 NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed and Flashover	
<b>CE Certification</b>	EU classification in accordance with EN 15102:2007 + A1:2011	
<b>Indoor Air Quality</b>	California 01350 – Meets emission requirements for schools and offices	
<b>Repeat</b>	Vertical	N/A
	Horizontal	N/A
	Nominal Information	51”
	Match Information	Random Match, Reverse Hang
1	When applied to GRC board with A-848-B adhesive	
2	When applied to 5/8” Type-X-Gypsum board with A-848-B adhesive	