

Flex™ Decorative Wall Protection

3875 Embassy Parkway
Fairlawn, OH 44333
855.753.5474 | koroseal.com

Thatch

FACT SHEET

Thatch is enhanced with the colors of a painter's palette. The troweled vertical lines of the texture pick up the colors in rich, brilliant tones. Thatch reminds us of the stolen beauty of the past colored to perfection.

	US UNITS	METRIC UNITS
Total Weight	35 oz. PLY 22.4 oz. PSY	992 g PLM 635 g PSM
Roll Width	52 in.	132 cm.
Backing	Woven	
Federal Spec.	CCC-W-408D, Type III	
WA Spec.	WA-101, Type III	
ASTM F-793	Category VI, Type III	
Fire Testing	ASTM E-84, CAN S102M Tunnel Test ¹ Class A Rating NFPA 286 - Meets 2006 IBC Section 803.2.1	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical Horizontal Nominal Information Match Information	N/A N/A 52 in. Straight Match, Reverse Hang

¹ When applied to GRC board with A-848-B adhesive

Available in 8 Colorways

THA1-10 Earnest
THA1-09 Portrait
THA1-37 Expectation
THA1-91 Poplar
THA1-21 Hope
THA1-53 Birch Forest
THA1-43 Sepia
THA1-98 Smoke