Koroseal® DEALS

3875 Embassy Parkway Fairlawn, OH 44333

855.753.5474 koroseal.com

DEALS V419 FACT SHEET

US UNITS METRIC UNITS

Nominal Weight 16.0 oz PLY 500 g PLM

10.7 oz PSY 360 g PSM

Weight Savings Absence of chlorine provides a lower molecular weight polymer,

therefore, making the wallcovering lighter for the same thickness.

-Reduced freight costs

-Easier handling of rolls for safety

Roll Width 54/55 in. 134/140 cm

Fabric Non-Woven

Washability/Scrubability Meets 300 Cycle Requirements

Stain Resistance Premium stain and abrasion resistant water-based coating applied

Post Consumer Recycled Content Contains a minimum of 20%

Fire Testing NFPA 101[®] Life Safety Code[®]

NFPA 255 (UL723, CAN S102M) Tunnel Test¹

Class A Rating NFPA 286 Corner Burn Test²

Meets requirements for Flame Spread, Smoke Developed and

Flashover

Combustion Toxicity Pittsburgh Protocol - Meets the New York City Requirements

Indoor Air Quality California 01350 - Tested to and meets emission requirements for schools

and offices.

Repeat Vertical 31.25 in. 79.4 cm

Horizontal 26 in. 66 cm Nominal Pattern Width 52 in. 132 cm

Match Information Match Pattern, Non-Reverse Hang

Does not contain chlorine or other halogen compound. Contains no plasticizers including phthalates. Printing inks are water-based.

1 When applied to GRC Board with A-848-B adhesive 2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

Available in 2 Colorways

*V419-45

*V419-66

^{*}These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.