

The silk like look and texture of Axis is the foundation pattern for an exciting group of companion designs all taking inspiration from geometry. Symmetry is the large scaled design of overlapping circles created through the use of reflection while line of symmetry is a tiny ribbed pinstripe. The final design of this grouping is Vertex, a small geometric texture made of angular lines creating small diamond shapes. This group of designs offers a great many possibilities to the designer with its usable palette.

	US UNITS	METRIC UNITS
Total Weight	20.0 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
Roll Width	53/55 in.	134/140 cm
Gauge (avg)	0.22 in.	0.56 mm
Fabric	Nonwoven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	111 x 111 N
Federal Spec	CCC-W-408D, Type II	
WA Spec	WA-101, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating Flame Spread 10 Smoke Developed 5 NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover EU classification in accordance with EN 13501-1:2007 and EN-15102-2008	
Indoor Air Quality	California 01350 - Meets emission requirements for schools and offices	
Repeat	Vertical N/A Horizontal N/A Nominal Pattern Width 52 in. Match Information Random Match, Reverse Hang	132 cm
	1 When applied to GRC Board with A-848-B adhesive	2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 20 Colorways

1922-29 Alabaster	1922-68 Marsala	1922-57 Smokey
1922-53 Champagne*	1922-77 Midnight	1922-92 Sterling
1922-81 Daybreak	1922-55 Molten*	1922-65 Sunset
1922-59 Eclipse	1922-25 Moonlight	1922-38 Whisper
1922-69 Espresso	1922-36 Mystic	
1922-20 Eternity	1922-01 Purity	
1922-47 Guilded*	1922-90 Shadow	
1922-75 Indigo	1922-40 Sincerity	

*** These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.**

Vinyl wallcovering has a multitude of characteristics that allow it to provide an attractive and serviceable wall surface. One of the characteristics of vinyl wallcoverings is very low moisture permeability. Therefore, it is important to assure that there are no deficiencies in the design, construction and maintenance of a building that allows moisture to accumulate in a wall cavity. The use of a vinyl wallcovering in such a deficient circumstance would result in the vinyl wallcovering acting as a vapor barrier and restricting the passage of the moisture and increasing the chance of mold growth. It is recommended that walls be checked with a suitable moisture meter prior to installation and the moisture content should not exceed 4%. Wallcovering should not be installed on a wall until water/moisture incursion has been eliminated. On renovation projects, examine walls that are to receive wallcovering and assure they do not exhibit any mold/mildew. All mold and mildew must be removed and surfaces treated to inhibit future growth. In order to reduce the risk of mold/mildew, Koroseal Interior Products utilized an inhibitor in the wallcovering. The company can also provide a service of microventing the wallcovering whereby more than 25,000 micro-holes /ft² are fused through the vinyl thereby making it permeable.