



koroseal®

CLODAGH **WEATHERED ALLOY**
Fact Sheet**8 Colorways:**CL08-01 Sleet
CL08-02 Breeze
CL08-03 Dew
CL08-04 FogCL08-05 Blizzard
CL08-06 Haze*
CL08-07 Rainfall
CL08-08 Thunder

*This decorative metallic wallcovering should only be cleaned with mild ingredients such as soap, detergent, and water.
Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	18 in.
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	52 in.
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Non-Reverse Hang, Straight Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

NFPA 101® Life Safety Code®

Fire TestingNFPA 255 (ASTM E-84, CAN S102M) Tunnel Test¹

- Class A Rating
- Flame Spread - 10
- Smoke Developed - 5

NFPA 286 Corner Burn Test²

- Meets requirements for Flame Spread, Smoke Developed, & Flashover

¹ When applied to GRC board with A-848-B adhesive ² When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011**Indoor Air Quality** California 01350 – Meets emission requirements for schools and offices**3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com**

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
©2023 Koroseal Interior Products, LLC.

46-47-CL08-11/2022