



8 Colorways:

- THA1-09 Portrait
- THA1-10 Earnest
- THA1-21 Hope
- THA1-37 Expectation
- THA1-43 Sepia
- THA1-53 Birch Forest
- THA1-91 Poplar
- THA1-98 Smoke

Designer	Koroseal		
Total Weight	35.0 oz. ply (1082 g. plm.) 22.4 oz. psy (635 g. psm.)	Vertical Repeat	N/A
Roll Width	52 in. (132 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	52 in.
Tensile (Minimum)	N/A	Match Information	Reverse Hang, Straight Match
Tear (Minimum)	N/A	WA Spec.	WA-101, Type III
Federal Spec.	CCC-W-408D, Type III	ASTM F-793	Category VI, Type III
Fire Testing	NFPA 101® Life Safety Code®		
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating		
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, and Flashover		
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices		
For additional technical information please visit koroseal.com			

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
 Flex™ is a trademark of Koroseal Interior Products, LLC.
 NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
 ©2024 Koroseal Interior Products, LLC.