COMFORT ZONE PET FELT SPEC SHEET



COMPOSITION:

- 100% Polyethylene Terephthalate (PET)
- 55% Recycled Content

APPLICATION:

- Sound Insulation
- Sound Absorption

SIZES:

Variable custom sizes up to 48"x96"

THICKNESS:

- 9mm or I2mm standard
- Variable custom thickness to 24mm

SOUND ABSORPTION:

ASTM C423 - .75 NRC

ENVIRONMENTAL HEALTH FACTORS:

- Low VOC emissions
- ASTM D5II6

RECYCLABILITY:

• 100% Recyclable

CREDITS LEED:

MRc4

CLASSIFICATION:

• 09 84 00 Acoustic Room Components

DETAILS:

PRODUCT DESCRIPTION: PET Felt acoustic panels and tiles add color and style to any space while absorbing extra noise. PET Felt panels and tiles are manufactured using recycled PET plastic bottles, eco-friendly dyes and no added adhesive, resulting in a Green Tag-certified product that can help qualify for LEED green building credits. This HPD covers PET Felt in all available colors.

POLYETHYLENE TEREPHTHALATE (PET) (POLYETHYLENE TEREPHTHALATE (PET)) LT-UNK 7H-BENZO[E]PERIMIDINE-4CARBOXAMIDE, N-(9,10-DIHYDRO-9,10-DIOXO-I- ANTHRACENYL)-7OXO- LT-UNK BISMUTH VANADIUM TETRAOXIDE LT-PI | MUL C.I. PIGMENT BLUE I5 BM-3 ULTRAMARINE (PIGMENT) LT-UNK 5,12DIHYDROQUINO(2,3-B) ACRIDINE-7,14-DIONE LT-UNK CARBON BLACK LT-I | CAN I,4-DIHYDROXYANTHRAQUINONE LT-UNK PERYLENE RED NoGSTITANIUM DIOXIDE (TITANIUM DIOXIDE) LT-I | CAN | END]

INSTALL METHODS:

Construction Panel Adhesive, Carpet Glue or Nail Clips with Adhesive

CERTIFICATIONS AND COMPLIANCE

VOC emissions: CDPH Standard Method VI.2 (Section 0I350/CHPS) Classroom & Office scenario

Multi-attribute: GreenTag 3.1 - Gold - GreenRate Level A

LCA: ISO I4040:2006 Environmental management - Life cycle assessment Recycled content: TE Global Recycle Standard - V2.I

Consistency with other programs: Pre-checked for LEED v4 Material Ingredients, Option

MATERIAL THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES CONSIDERED: Yes

RESIDUALS AND IMPURITIES NOTES: No residuals or impurities are known or expected to be present at or above the Inventory Threshold indicated for the finished product that would trigger a GS score of BM-I, LT-I, LT-PI or NoGS based on supplier statements, supplier SDS, and as predicted by process chemistry (Pharos CML).

POLYETHYLENE TEREPHTHALATE (PET) %: 97.2000 - 99.5000 GS: LT-UNK RC: PostC

NANO: No

ROLE Substrate: Provides structure and rigidity

HAZARDS AGENCY(IES) WITH WARNINGS: None Found No warnings found on HPD Priority lists

SUBSTANCE NOTES: Comfort Zone is made with up to 60 percent post-consumer recycled PET from a variety of sources (e.g. PET bottles). Certificate of Compliance for recycled fibers, as inspected and assessed according to the Global Recycle Standard (GRS) Version 2.I (Control Union Certifi cations; I2 August 2013).

FLAME RATING: Fella Felt is available in Class A and Class B Fire Rating as per ASTM E84-I7



9mm FINISHES



07 White



12mm FINISHES



73-12 Heathered Mustard



68-12 Heathered Amber



45-12 Big Red



77-12 Heathered Violet



21-12 Indigo Blue



39-12 Green Apple



05-12 Dark Green



70-12 Heathered Foliage



72-12 Heathered Lagoon



76-12 Heathered Teal



71-12 Heathered Granite



75-12 Heathered Oatmeal



02-12 Taupe



63-12 Medium Gray



17-12 Dark Gray



34-12 Pure Gray



78-12 Heathered Quartz



10-12 True Black



03-12 Light Gray



74-12 Heathered Slate



07-12 White