



20 Colorways:	T123-01 Parchment	T123-09 Sagebrush	T123-44 Teak
	T123-02 Simply White	T123-10 Indigo	T123-46 Beam
	T123-03 Sky	T123-11 Ebony	T123-48 Walnut
	T123-04 Driftwood	T123-13 Glazed	T123-50 Rosewood
	T123-05 Saddle	T123-14 Maple	T123-95 Smoked
	T123-06 Sandstone	T123-16 White Oak	T123-99 Charred
	T123-07 Graphite	T123-42 Ash	

Designer	Koroseal		
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb <sub>f</sub> (222 x 245 N)	Match Information	Non-Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb <sub>f</sub> (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

NFPA 101® Life Safety Code®

Fire Testing

NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test<sup>1</sup>  
- Class A Rating

NFPA 286 Corner Burn Test<sup>2</sup>  
- Meets requirements for Flame Spread, Smoke Developed, & Flashover

<sup>1</sup> When applied to GRC board with A-848-B adhesive    <sup>2</sup> When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification    EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality    California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit [koroseal.com](http://koroseal.com)

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | [koroseal.com](http://koroseal.com)

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.  
©2024 Koroseal Interior Products, LLC.